



6. In an input/output circuit according to claim 5, the further improvement wherein the AM signal utilizes a carrier generated by a fixed duty cycle output of the aforesaid modulator.

7. Isolation logic for use in transferring information over a transformer between first and second control devices, the isolation logic comprising

a modulator that generates a pulse width modulated (PWM) signal encoding an analog frequency shift keying (FSK) signal to be transferred between the first and second control devices, and

the modulator being coupled to the transformer and applying the PWM signal thereto.

8. Isolation logic according to claim 7, wherein

the modulator is associated with a first one of the control devices,

the modulator applies the PWM signal to the transformer to effect transfer of the FSK signal encoded therein from the first control device to the second control device.

9. Isolation logic according to claim 8, wherein the modulator is coupled to a modem that generates the FSK signal to be transferred

10. Isolation logic according to claim 9, wherein

the modem is coupled to the first control device and receives therefrom a digital signal containing information to be transferred from the first control device to the second control device,

the modem generates the FSK signal from the digital signal.

11. Isolation logic according to any of claims 7 - 10, wherein each of the first and second control devices include any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control.
12. Isolation logic according to any of claims 7 - 10, wherein the FSK signal is compatible with any of a FoxComm™, HART™ or other analog control signal format.
13. Isolation logic according to any of claims 7 - 10 adapted for galvanic isolation across an isolation barrier.
14. An input/output module for use in any of industrial, manufacturing, service, environmental, or process control to transfer information over an isolation barrier between first and second control devices, the isolation logic comprising  
  
transformer logic that inductively transfers a pulse width modulated (PWM) signal across the isolation barrier, the PWM signal having encoded therein an analog frequency shift keying (FSK) signal being transferred from the first to the second control device, and  
  
the transformer logic inductively transferring an amplitude modulated (AM) signal across the isolation barrier, the AM signal having encoded therein an analog FSK signal being transferred from the second to the first control device.
15. An input/output module according to claim 14, wherein the transformer logic includes a first transformer that inductively transfers the PWM signals and second transformer that inductively transfers the AM signals.

16. An input/output module according to claim 14, comprising a first modulator that is coupled to the transformer logic, the first modulator generating and applying to the transformer logic the PWM signal during a period in which an FSK signal is to be transferred from the first control device to the second control device.
17. An input/output module according to claim 16, wherein the first modulator generates and applies to the transformer logic a signal of fixed duty cycle during a period in which an FSK signal is not being transferred from the first control device to the second control device.
18. An input/output module according to claim 17, comprising a second modulator that is coupled with the transformer logic, the second modulator generating the AM signal utilizing the signal of fixed duty cycle as a carrier signal.
19. An input/output module according to claim 18, wherein  
  
the second modulator is coupled to the second control device and receives therefrom an FSK signal encoding information to be transferred from the second control device to the first control device, and  
  
the second modulator generates the AM signal by modulating the carrier signal in accord with the FSK signal received from the second control device.
20. An input/output module according to claim 19, wherein the second modulator generates the AM signal by multiplying the carrier signal by the FSK signal received from the second control device.
21. An input/output module according to any of claims 14 - 20, wherein the FSK signal is compatible with any of a FoxComm™, HART™ or other analog control signal format.

22. An input/output module according to any of claims 14 - 20, wherein each of the first and second control devices include any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control.

23. A control system comprising,

a first control device and a second control device, each of the first and second control devices including any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control,

a first analog source that generates a first analog frequency shift keying (FSK) signal encoding information for transfer from the first control device to the second control device,

a first modulator that is coupled to the first analog source, the first modulator generating a pulse width modulated (PWM) signal having encoded therein the first FSK signal,

a second analog source that generates a second analog FSK signal encoding information for transfer from the second control device to the first control device,

a second modulator that is coupled to the second analog source, the second modulator generating an amplitude modulated (AM) signal having encoded therein the second FSK signal,

first and second transformers that are coupled to the first and second modulators, respectively, the first and second transformers inductively carrying the PWM and AM signals, respectively, across an isolation barrier.

24. A control system according to claim 23, comprising a first demodulator that is coupled to the transformer, the first demodulator responding to the PWM signal carried by the transformer to generate an FSK signal encoding the information being transferred from the first control device to the second control device.
25. A control system according to claim 24, comprising a second demodulator that is coupled to the transformer, the second demodulator responding to the AM signal carried by the transformer to generate an FSK signal encoding the information being transferred from the second control device to the first control device.
26. A control system according to claim 25, wherein  
  
the first analog source, the first modulator, and the second demodulator are associated with the first control device, and  
  
the second analog source, the second modulator and the first demodulator are associated with the second control device.
27. A control system according to claim 25, wherein  
  
the first analog source, the first modulator, and the second demodulator are disposed on a same side of the isolation barrier as the first control device, and  
  
the second analog source, the second modulator and the first demodulator are disposed on a same side of the isolation barrier as the second control device.



inductively transferring a pulse width modulated (PWM) signal across the isolation barrier, the PWM signal having encoded therein an analog frequency shift keying (FSK) signal containing information being transferred from the first to the second control device, and

inductively transferring an amplitude modulated (AM) signal across the isolation barrier, the AM signal having encoded therein a FSK signal containing information being transferred from the second to the first control device.





including any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control,

generating a pulse width modulated (PWM) signal having encoded therein the first FSK signal,

generating a second FSK signal encoding information for transfer from the second control device to the first control device,

generating an amplitude modulated (AM) signal having encoded therein the second FSK signal,

inductively transferring the PWM and AM signals across an isolation barrier.

47. A method of operating a control system according to claim 46, comprising responding to the PWM signal transferred by the transformer to generate a further FSK signal encoding the information being transferred from the first control device to the second control device.
48. A method of operating a control system according to claim 47, comprising responding to the AM signal transferred by the transformer to generate a further FSK signal encoding the information being transferred from the second control device to the first control device.
49. A method of operating a control system according to any of claims 44 - 48, wherein the FSK signals are compatible with any of a FoxComm™, HART™ or other analog control signal format.
50. A method of operating a control system according to any of claims 44 - 48, wherein each of the first and second control devices include any of a workstation, field controller, field device, smart field device, or other device for any of industrial, manufacturing, service, environmental, or process control.